

LICENCE CONDITIONS

© Crown in right of New South Wales



The data supplied is licensed under a Creative Commons Attribution licence. To view a copy of this licence, visit

<http://creativecommons.org/licenses/by/4.0>

The Creative Commons Attribution Licence is available in [plain English text](#) <https://creativecommons.org/licenses/by/4.0> and a [full legal code](#) <http://creativecommons.org/licenses/by/4.0/legalcode>

Licence:

This work is licensed under a Creative Commons Attribution 4.0 Licence: <http://creativecommons.org/licenses/by/4.0/legalcode>

You are free: to copy, distribute, display, and perform the work; to make derivative works and to make commercial use of the work,

Under the following conditions: Attribution — You must give the original author credit. Please attribute "NSW Office of Environment and Heritage" in any publications using this data.

Legal

Errors and Omissions in the Product - The Licensee acknowledges that the Product has not been fully tested by the Licensor and may contain omissions and errors and that it must rely on its own examination, skill and expertise in determining whether the Product is capable, suitable or safe for a particular application and use. The Licensor makes no guarantee to provide upgrades of the Product to the Licensee. The Licensee acknowledges that the Product has not been developed for use on the Licensee's own software and that the Licensor makes no warranties in relation to the Licensee's software being able to utilise the Product. The Licensee must rely on its own skill and expertise in determining whether it will be able to utilise the Product.

Liability - The Licensee hereby releases and indemnifies, and will keep harmless and indemnified, the Licensor from and against all liability whatsoever arising out of the use of the Product or otherwise whether for breach of this Agreement by the Licensor, negligence, injury, death, economic loss, loss of reputation or damages incidental or consequential to the provisions of this Agreement.

QUALITY CODE DESCRIPTIONS

Quality Code		Water Level*	Rainfall	Barometric Pressure*	Temperature*	Conductivity*
5 (Very Good)	Records processed to	±5mm	±3% of calibration	±0.5mbar	±0.5°C	±2mS/m
6 (Good)	Records processed to	±6mm		±1mbar	±1.0°C	±2mS/m
55 (Fair)	Records processed to	±20mm	±5% of calibration	±2mbar	±2.0°C	±5mS/m
100 (Least Code)	Data from previous MHL database, processed to	±20mm	±3% of calibration	±1mbar		
105 (Poor)	Records processed to	±50mm	±10% of calibration	±5mbar	±5.0°C	±10mS/m
208 (Very Poor)	Records processed to greater than	±50mm	±10% of calibration	±5mbar	±5.0°C	±10mS/m
41 (Fitted Data)	Fitted data					
150 UnCoded)	Uncoded – data not yet quality controlled	Raw data from the instrument with only preliminary quality checks performed				
161, 204, 205, 206, 207, 255 (Data Loss or Missing Data)	Data loss					

* A quality code is assigned under the conditions that at least 95% of the data meets the quality code requirements, based on single point calibration

GAPS AND MISSING DATA

Gaps in the data record can be caused for many reasons and few data stations have a complete unbroken record of data. Gaps may be due to equipment damage, telemetry or logger problems or other site issues.

TIME

All times are Australian Eastern Standard Time (EST) accurate to ±2 minutes unless otherwise specified. Allowance for daylight saving time needs to be made by the user of the data if required.

ACCURACY AND RESOLUTION

The resolution of data is usually higher than the accuracy. A sensor may record data to 3 decimal places but the data value may only be accurate to 2 decimal places due to systematic and random uncertainties involved in the collection of the data.

DATA FIT FOR PURPOSE

General Guidelines

Tidal data is subject to a range of influences that may be desirable for the end user, or considered as noise. Seicheing for example may be the subject of study for one user, but unwanted noise for another. Some processes (wind waves for example) are filtered out by measurement and sampling technique. Similarly flood events have not been removed from river entrance datasets. It is MHL policy to leave recorded data as untouched as possible allowing the record available for many different purposes.

The end user of the data needs to determine the suitability of the data record for the research question being considered and its fitness in terms of quality. The user will need to analyse the extent to which these datasets match or miss the suitability and fitness expected. Depending on the suitability of the dataset and its quality the user may have to reformulate or relax the research question and make a final decision to accept or reject the outcome of the analysis after consideration of qualitative and quantitative measure of the data.

The following paragraphs outline some of the main points to consider when determining if the data is fit for purpose.

Correction with Validation Readings - the raw data from the instrument is quality controlled using observer readings from visits to the site. The data is adjusted, if required, using the observer readings of the actual water level against a known datum. Further checks are made against the backup sensor at the site, the predicted and residual data and nearby sites if necessary. Floods are not removed from the river entrance site datasets.

Missing data - if there is missing data in the gauge record, where possible it is recovered and filled from the backup sensor at the site. If only a single point is missing then the data is interpolated linearly between the adjacent points. Other than these two cases missing ocean tide data is not in-filled or reconstructed.

Systematic Issues – some instrumentation has been known to over or under range data particularly on the low or high points of the tide. This is generally identified by comparison with prediction. The over-ranging values have been removed but the correct data has been left in the record. This may mean there are periods of data where there are a significant number of high or low points in the tide missing. This is problematic for means and median analysis and sea level trends.

Quality Coding –Data is quality coded as part of the quality assurance procedure. The codes are shown on the previous page. Data coded 100 LeastCode or 55 Fair or better is generally issued but data of poorer quality may be available on request. Data coded poor or very poor usually indicates unresolvable issues such as possible datum offsets, unquantified instrument issues or systematic issues as described above. Any data coded poor or very poor should be carefully considered before it is used in analyses.

Datums - many ocean tide level gauges are recorded in the local port datum which generally equates to Indian springs low water (ISLW). An indicative adjustment of each station datum level to the local Australian Height Datum (AHD) is shown in the accompanying table. These adjustments were calculated circa 1990 for MHL by NSW Public Works Survey, using tidal harmonic analysis over a tidal epoch. These values should be used with caution, as AHD levels are revised from time to time and improvements to GPS surveying techniques may provide additional refinement. Offshore sites are not related to a datum, but provide valuable astronomical constituent information and anomalies. Norfolk Island and Lord Howe Island are recent installations that were not included in the original datum adjustment review.

Tides are not stationary – it is prudent to keep in mind during analysis of tidal records that tides are not stationary. The major constituents are not constant nor is the mean sea level (Zo). Variations in these components can have significant impact when research involves comparing long term trends or analyses between different time periods of data.

Prediction and Anomalies – MHL predictions are calculated using the Foreman versatile method. The prediction method together with the time period used for the analysis can significantly impact on the results. Any anomalies (or residuals) can suffer similar impacts.

If there are significant non-astronomical influences in the tidal records then predictions that don't take into account these oceanographic processes can affect the accuracy of the prediction in comparison to actual measured water levels.

Similarly river entrance and upstream morphological changes will impact on the accuracy of any tidal predictions. Predictions conducted during one morphological condition will not be accurate for other morphological conditions in the estuary.

Due to these limitations predictions should be considered in the nature of a general guide only and should not be relied upon in any critical situation, nor used for navigation. To the greatest extent permitted by law NSW Public Works excludes all liability for any loss or damage (including damage caused by negligence) incurred by any person/organisation directly or indirectly as a result of usage of this information and usage of the information is done at their own risk.

DATUM ADJUSTMENT

Each ocean tide level gauge is recorded in the local port datum which generally equates to Indian Springs Low Water (ISLW). An indicative adjustment of each station datum level to the local Australian Height Datum (AHD) is shown in the table below. These adjustments were calculated circa 1990 for MHL by NSW Public Works Survey Branch, using tidal harmonic analysis over a tidal epoch. These values should be used with caution, as AHD levels are revised from time to time and improvements to GPS surveying techniques may provide additional refinement. Offshore Aanderaa sites are not related to a datum, but provide valuable astronomical constituent information and anomalies. Norfolk Island and Lord Howe Island are recent installations that were not included in the original datum adjustment review and use local datums.

Summary of Adjustment to AHD

Station	Station Datum (SD)	Adjustment (SD - Adjustment = AHD)
Tweed Entrance South	Tweed River Hydro Datum	0.893
Tweed Heads Offshore	Mean Sea Level	NA
Brunswick Heads	Brunswick River Flood Mitigation Datum	0.046
Ballina Breakwall	Richmond River Valley Datum	0.860
Yamba	Iluka Port Datum	0.895
Yamba Offshore	Mean Sea Level	NA
Lord Howe Island	Lord Howe Island Hydro Datum	NA
Norfolk Island	Norfolk Island Tidal Datum	NA
Coffs Harbour	Coffs Port Datum	0.882
Port Macquarie	Australian Height Datum	0.000
Port Macquarie Offshore	Mean Sea Level	NA
Crowdy Head	Crowdy Head Datum	0.911
Forster	Forster Hydro Datum	1.061
Port Stephens	Port Stephens Hydro Datum	0.944
Patonga	Australian Height Datum	0.000
Sydney	Zero Fort Denison	0.925
Fort Denison (Sydney Ports)	Zero Fort Denison	0.925
Bundeena (Port Hacking)	Zero Fort Denison	0.925
Shoalhaven Offshore	Mean Sea Level	NA
Crookhaven Heads	Australian Height Datum	0.000
Jervis Bay	Chart Datum	1.070
Ulladulla	Australian Height Datum	0.000
Princess Jetty	Australian Height Datum	0.000
Batemans Bay Offshore	Mean Sea Level	NA
Bermagui	Bermagui Local Hydro Datum	0.714
Eden Boat Harbour	Twofold bay Hydro Datum	0.924